

A white TitanHz ANPR camera is mounted on a street at night. The camera is positioned in the upper left quadrant, with its lens and sensor array visible. The background shows a city street with traffic lights and buildings illuminated at night. The TitanHz logo is printed on the side of the camera housing.

titanHz

The **titanHz** is a latest generation **ANPR system**, designed to read license plates in movement. The Professional series automatic number plate recognition system can capture the number plate at the speed of **200 km**. titanHz ANPR system supports all GCC Number Plates

JE3989EF-V

titanHz ANPR Camera

TECHNICAL FEATURES

- High quality imaging with 4 MP resolution
- Excellent low-light performance
- Clear imaging against strong back light due to 140 dB WDR technology
- Efficient H.265+ compression technology to save bandwidth and storage
- Motorized 2.8 - 12mm lens
- Water and dust resistant (IP67) and vandal proof (IK10)

TECHNICAL SPECIFICATION

Camera	
Image Sensor	1/1.8" Progressive Scan CMOS
Max. Resolution	2688 × 1520
Min. Illumination	Color: 0.0005 Lux @ (F1.2, AGC ON); B/W: 0.0001 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1 s to 1/100,000 s
Day & Night	IR cut filter Blue glass module to reduce ghost phenomenon
Lens	
Focal Length & FOV	2.8 to 12 mm, horizontal FOV: 114.5° to 41.8°, vertical FOV: 59.3° to 23.6°, diagonal FOV: 141.1° to 48°
Focus	Auto, semi-auto, manual
Iris Type	P-iris
Aperture	2.8 to 12 mm: F1.2 to F2.5
DORI	
DORI	Wide: 2.8 to 12 mm: D: 60 m, O: 23.8 m, R: 12 m, I: 6 m Tele: 2.8 to 12 mm: D: 149 m, O: 59.1 m, R: 29.8 m, I: 14.9 m
Image	
Image Parameters Switch	Yes
Image Settings	Saturation, brightness, contrast, sharpness, gain, white balance adjustable by client software or web browser
Day/Night Switch	Day, Night, Auto, Schedule, Alarm Trigger, Video Trigger
Wide Dynamic Range (WDR)	140 dB
SNR	≥ 52 dB
Image Enhancement	BLC, HLC, Defog, 3D DNR
Picture Overlay	LOGO picture can be overlaid on video with 128 × 128 24bit bmp format
Image Stabilization	EIS
General	
Power	12 VDC ± 20%, 1.19 A, max. 14.28 W, three-core terminal block PoE: 802.3at, Type 2, Class 4, 42.5 V to 57 V), 0.396 A to 0.295 A, max. 16.8 W
Material	Aluminium alloy body
With Package Weight	4kg
Storage Conditions	-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Startup and Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F). Humidity 95% or less (non-condensing)
General Function	Anti-flicker, 5 streams, EPTZ, heartbeat, mirror, privacy mask, flash log, password reset via email, pixel counter





Mailing Address

VOSTOK Trading L.L.C.
304, 3rd Floor, Al Tawhidi Building,
Khaleed Bin Waleed Road,
P.O. Box: 27106 - Dubai,
UNITED ARAB EMIRATES.

Contact Details

Tel : (+971 4) 3558816
Fax : (+971 4) 3558817
Web : www.titanhz.com
Email : sales@titanhz.com

Social Media

 www.facebook.com/pages/Titanhz/151150798404988
 plus.google.com/112635276746321262748/posts
 titanhz-anpr-systems.blogspot.in
 twitter.com/titanHz